

MAST SPECIFICATIONS and RATED CAPACITIES

D80S-9

Shaft Type Carriage (Without Sideshifter, Without Fork Mover)					Rated Load Capacities		
Mast type	Maximum fork height	Maximum lowered height	Fully extended height	Free lift	D80S-9		
					Double Pneumatic		
					Tilt Angle		Load Capacities
					with load backrest	with load backrest	LC 600mm
mm	mm	mm	mm	deg	deg	kg	
STD	3,100	2,835	4,375	215	15	10	8,000
	3,300	2,935	4,575	215	15	10	8,000
	3,600	3,085	4,875	215	15	10	8,000
	4,100	3,435	5,375	215	15	10	8,000
	4,600	3,685	5,875	215	15	10	8,000
	5,100	3,935	6,375	215	15	10	8,000
	5,400	4,085	6,675	215	15	10	8,000
	5,600	4,185	6,875	215	15	10	7,800
	6,500	4,735	7,775	215	15	10	7,400
FFT	4,350	2,630	5,625	1,420	15	10	8,000
	4,800	2,780	6,075	1,570	15	10	8,000
	5,400	2,980	6,675	1,770	15	10	7,750
	5,850	3,130	7,125	1,920	15	10	7,500
	6,540	3,410	7,815	2,200	15	10	7,100
	7,650	3,780	8,925	2,570	15	10	5,400
FFTC	4,350	2,630	5,625	1,420	15	10	8,000
	4,800	2,780	6,075	1,570	15	10	8,000
	5,400	2,980	6,675	1,770	15	10	8,000
	5,850	3,130	7,125	1,920	15	10	7,500
	6,540	3,410	7,815	2,200	15	10	7,100
	7,650	3,780	8,925	2,570	15	10	5,400

D90S-9

Shaft Type Carriage (Without Sideshifter, Without Fork Mover)					Rated Load Capacities		
Mast type	Maximum fork height	Maximum lowered height	Fully extended height	Free lift	D90S-9		
					Double Pneumatic		
					Tilt Angle		Load Capacities
					with load backrest	with load backrest	LC 600mm
mm	mm	mm	mm	deg	deg	kg	
STD	3,100	2,835	4,375	215	15	10	9,000
	3,300	2,935	4,575	215	15	10	9,000
	3,600	3,085	4,875	215	15	10	9,000
	4,100	3,435	5,375	215	15	10	9,000
	4,600	3,685	5,875	215	15	10	9,000
	5,100	3,935	6,375	215	15	10	9,000
	5,400	4,085	6,675	215	15	10	8,900
	5,600	4,185	6,875	215	15	10	8,750
	6,500	4,735	7,775	215	15	10	8,200
FFT	4,350	2,630	5,625	1,420	15	10	9,000
	4,800	2,780	6,075	1,570	15	10	9,000
	5,400	2,980	6,675	1,770	15	10	8,700
	5,850	3,130	7,125	1,920	15	10	8,350
	6,540	3,410	7,815	2,200	15	10	7,900
	7,650	3,780	8,925	2,570	15	10	5,400
FFTC	4,350	2,630	5,625	1,420	15	10	9,000
	4,800	2,780	6,075	1,570	15	10	9,000
	5,400	2,980	6,675	1,770	15	10	8,700
	5,850	3,130	7,125	1,920	15	10	8,350
	6,540	3,410	7,815	2,200	15	10	7,900
	7,650	3,780	8,925	2,570	15	10	5,400

Note : Mast Specifications & Rated Capacities are based on standard chassis with pneumatic tire and without side shifter.



D60S-9 / D70S-9 / D80S-9 / D90S-9

9-SERIES FORKLIFTS

Pneumatic Diesel 6.0 to 9.0 tonne capacity

Euro Stage V



UKD70S9-EN v1 (November 2021)



Doosan Industrial Vehicles UK Limited

12 Kilvey Road
Brackmills Industrial Estate
Northampton, NN4 7BQ

Tel.: 01604 825 600
Website: www.doosanfit.com

Authorised Dealer

